DMS - 8142

PAINTABLE CAULK FOR CONCRETE AND STEEL

EFFECTIVE DATE: OCTOBER 2014

- **8142.1. Description.** This Specification governs and defines paintable caulk for use on existing concrete or painted steel.
- **8142.2.** Units of Measurements. The values given in parentheses (if provided) are not standard and may not be exact mathematical conversions. Use each system of units separately. Combining values from the two systems may result in nonconformance with the standard.
- **8142.3. Material Producer List.** The Materials and Pavements Section of the Construction Division (CST/M&P) maintains the Material Producer List (MPL) of all materials conforming to the requirements of this Specification. Materials appearing on the MPL, entitled "Paintable Caulk for Concrete and Steel," do not require further testing, unless deemed necessary by the Engineer.
- **8142.4.** Bidders' and Suppliers' Requirements. The Department will only purchase or allow on projects those products listed by manufacturer and product code or designation shown on the MPL.

8142.5. Pre-Qualification Prodcedure.

A. Pre-Qualification Request. Submit a request for evaluation under DMS-8142 to the Texas Department of Transportation, CST/M&P (CP-51), 9500 North Lake Creek Parkway, Austin, TX 78717.

Include the following with the request:

- safety data sheet (SDS) that complies with OSHA Hazard Communication Standard 29 CFR 1910.1200;
- product data sheet;
- application data sheet; and
- test report showing that the material meets the requirements specified in Article 8142.6.
- **B. Evaluation.** The Department will evaluate one sample at no cost to the producer. The producer will bear the cost associated with additional testing necessary to establish specification compliance. The Director of CST/M&P will assess this cost at the time of evaluation.
 - **1. Qualification.** The Department will list materials meeting the requirements of this Specification on the MPL.
 - **2. Failure.** Producers not qualified under this Specification may not furnish materials for Department projects.

EFFECTIVE DATE: OCTOBER 2014

Producers failing to qualify may submit a request for re-evaluation after 6 mo. have elapsed from the date of the original request. CST/M&P may modify this time limit at its discretion. In the request for re-evaluation, the producer must document the cause of the issue and corrective action taken.

The Department normally bears the costs of sampling and testing; however, the producer will bear the costs associated with materials failing to conform to the requirements of this Specification. The Director of CST/M&P will assess this cost at the time of re-evaluation, and amounts due will be billed to the producer.

C. Formulation Changes. Report any changes in formulation to CST/M&P. The Department will evaluate one reformulation per year at no cost to the producer.

The Department reserves the right to conduct any tests deemed necessary to identify a qualified material and to determine if there has been a change in formulation. Detected changes not reported to the Department may be grounds for removal from the MPL.

Except for transition periods not to exceed 3 mo., a supplier may not supply more than one formula per type of caulk at the same time. Both Type S and Type M may be supplied at the same time.

- **D. Periodic Evaluation.** The Department reserves the right to perform random audits of test reports and to conduct random sampling and testing to evaluate the performance of materials. In case of variance, the Department's tests will govern. CST/M&P will select random samples from materials submitted to the Department on Contracts or direct State purchase orders. Failure to comply with the requirements of this Specification may be cause for removal from the MPL.
- **E. Disqualification.** Causes for disqualification may include, but are not limited to:
 - falsification of documentation,
 - failure to report formulation changes,
 - failure to meet the requirements of this Specification as a result of periodic evaluation, or
 - producer has unpaid charges for failing samples.

CST/M&P will remove disqualified producers from the MPL and will not allow submission of material for re-qualification for 6 mo., at the discretion of the Department.

F. Re-Qualification. Once the disqualification period established by CST/M&P has elapsed, producers disqualified and removed from the MPL may begin the re-qualification process by submitting a request in accordance with Section 8142.5.A, including additional documentation identifying the cause of the problem and corrective action taken. The requalification process will then follow all subsequent Sections of Article 8142.5.

The Department normally bears the costs of sampling and testing; however, the disqualified producer will bear the cost associated with re-qualification. The Director of CST/M&P will assess this cost at the time of re-evaluation, and amounts due will be billed to the producer.

8142.6. Material Requirements.

- **A. General Requirements.** Material may be single-component or multicomponent and formulated specifically for use in concrete and steel cracks. Material must cure to form a surface that is readily paintable with a variety of waterborne and solvent-borne coatings.
- **B. Testing.** Material must meet the requirements of ASTM C 920 for Grade NS and either Class 50 or Class 100/50.
- **C.** Consistency. The applied caulk must form a firm, continuous, uniform filled layer in a concrete crack or seam.

Caulk must have no skins, agglomerates, or other undesirable particles.

8142.7. Containers and Marking.

- **A. Packaging.** Ship materials in suitable strong, well-sealed containers that meet federal requirements and are that sufficiently sturdy to withstand normal shipping and handling.
- **B.** Labeling. Label the sides of the containers and cases with a durable label legibly printed with the following:
 - manufacturer name;
 - product designation, including component part (if applicable);
 - batch number;
 - date of manufacture; and
 - net volume or weight.

If palletized, boxed, or if other group packaging is used, maintain a label that is easily readable on the outside packaging.